



ORCP-WM-26-03

Call for Comments to the Proposed General Amendments on Additional Conditions for Qualifying a Frequency Driven Event (FDE)

The Rules Change Committee (RCC) is inviting all WESM Members and interested parties to submit comments to SNAP Group's Proposed General Amendments to the WESM Ancillary Services Monitoring Manual (ASMM) Issue 1.2 on Additional Conditions for Qualifying a Frequency Driven Event (FDE) (*ORCP-WM-26-03*).

The proposed amendment seeks to amend Section 5.6.2 of the ASMM by introducing an additional condition to determine the termination of an FDE, in view of the following:

- a. Give ample time for the Reserve Facility to normalize its loading near the Unit setpoint, which is the initial reference of the Unit governor in computing the desired response.
- b. Variances from the Reserve Facility's Frequency Reference compared to the System Frequency.
- c. Reduction of multiple Frequency Driven Events occurrences.

BACKGROUND:

The SN Aboitiz Power-Magat, Inc. and SN Aboitiz Power-Benguet, Inc. (collectively, the 'SNAP Group') submitted the proposed amendments on 24 March 2026 as an Urgent Amendment. Upon deliberation during its 257th Regular Meeting, the RCC determined that the proposal did not meet the urgency criteria and subsequently reclassified it as a General Amendment proposal. Consequently, the PEM Board, during its 95th Meeting on 29 April 2026, concurred with the RCC's decision on the said proposal.

DOCUMENTS:

Provided below are relevant materials for your reference and perusal:

- [Original Rules Change Proposal submitted by SNAP Group \(ORCP-WM-26-02\)](#)
- [Presentation of the Proposed Amendment](#)
- [PEM Board-approved proposal \(RCC Resolution No. 2026-03\) per PEM Board Approval on 29 April 2026](#)



- RCC Form 3: Matrix of Proposed Amendments for Comments – Annexes of this document *(Please write your comments in the proper columns in the matrix.)*

Kindly submit your comments (in Word format) through the '[File a Submission](#)' webpage no later than **16 June 2026** or 30 working days from the date of publication (04 May 2026). We recommend using Firefox browser for submitting your comments.

Please ensure that your submission is signed securely by the designated approving authority and/or representative of your company, and input in the proper field the e-mail address of your point person(s) whom we could contact regarding activities related to the processing of the proposal.

All comments received shall be published in the PEMC website.

Thank you!

Rules Review Division

Market Assessment Group

Philippine Electricity Market Corporation

+632 8631 8734 | mag_rrd@wesm.ph | www.wesm.ph

18F Robinsons Equitable Tower, ADB Avenue, Ortigas Center, Pasig City 1600, Philippines



TO BE ACCOMPLISHED BY THE PARTY SUBMITTING THE COMMENTS

[In accomplishing and submitting this form, you give your consent for PEMC to collect, record, organize, and update your personal data as herein provided as part of your information for purposes of rules change process.]

Commenter's Information

Name	Daryl Andrew M. Llana [Signature over Name]
Designation	Ancillary Services Manager
Company	San Miguel Global Power
Company Address	5th Floor, C5 Office Building Complex, 100 E. Rodriguez Jr. Ave., C5 Road, Ugong, Pasig City, 1604 Metro Manila
Telephone No.	
Email Address	

Comments to the Proposed General Amendments to WESM Ancillary Services Monitoring Manual Issue 1.2 on Additional Conditions for Qualifying a Frequency Driven Event (FDE)

Commenter	General Comments	Proponent's Response
	Please write your general comment here, if any.	

WESM ANCILLARY SERVICES MONITORING MANUAL 1.2

Title	Section	Provision	Proposed Amendment	Rationale	Comments	Proposed Wording based on Comments
Section 5.6 Measuring Reserve Response Compliance of Generators on	5.6.2.	<i>A reserve facility's</i> response accuracy via GCM shall be calculated as follows.¹² xxx The event will qualify as <i>Frequency-Driven Event</i>, for this purpose, if: a. the event lasts for more than five (5) seconds; and b. the frequency deviation exceeds the deadband setting by 0.02 Hz for conventional generating units and 0.01 Hz for battery energy storage systems. xxx	<i>A reserve facility's</i> response accuracy via GCM shall be calculated as follows.¹² xxx The event will qualify as <i>Frequency-Driven Event</i>, for this purpose, if: a. the event lasts for more than five (5) seconds; and b. the frequency deviation exceeds the deadband setting by 0.02 Hz for conventional generating units and 0.01 Hz for battery energy storage systems.; <u>c. the frequency deviation normalizes below the deadband setting by 0.02 Hz for conventional generating units and 0.01 Hz for battery energy storage; and</u>	To provide the Reserve Facilities an additional tolerance with the following considerations: a. Give ample time for the Reserve Facility to normalize its loading near the Unit setpoint, which is the initial reference of the Unit governor in computing the desired response. b. Variances from the Reserve Facility's Frequency Reference compared to the System Frequency c. Reduction of multiple Frequency Driven Events occurrences	Please also provide an illustration for Regulating Reserve (RR) demonstrating how the proposed FDE qualifier improves the response accuracy of an AS provider.	

WESM ANCILLARY SERVICES MONITORING MANUAL 1.2						
Title	Section	Provision	Proposed Amendment	Rationale	Comments	Proposed Wording based on Comments
			<u>d. the frequency deviation normalizes below the threshold for at least 25 seconds.</u> <u>For clarity, item (a) and item (b) determine the start of a FDE, while item (c) and item (d) determine the end of a FDE.</u> xxx	The additional provisions aim to combine the evaluation of multiple FDEs, and not exclude any FDE. This ensures that the system frequency has sufficiently recovered before registering a new event. It prevents premature triggering of multiple FDEs caused by short-lived or oscillatory frequency dips around the threshold.		